PUMPMASTER

DIGITAL PUMPMASTER DP2A-900-1 2 PUMP CONTROL WITH ALTERNATION



FEATURES


4.3" COLOR TOUCH DISPLAY LEAD- LAG CONTROLLER ALTERNATOR OVERRIDE ALARM HISTORY LIST LIGHTNING PROTECTION HAND-OFF-AUTO SWITCHES I/O LOGIC CONTROLLER
ALTERNATOR
HIGH ALARM
SUBMERSIBLE TRANSDUCER
RANGE 0-12, 0-24 FEET
NEMA 12 ENCLOSURE


OPTIONS

3, 4 PUMP CONTROLLER WITH ALTERNATION RADIO TELEMETRY, SCADA COMPATIBLE COMMUNICATION PORTS, ETHERNET INTERNAL DIALER, PRINTER OUTPUT CALL FOR OPTIONAL PRICING

DIGITAL PUMPMASTER

The Digital Pumpmaster is a sewage lift station controller which senses level in the sump and controls one or more pumps. The Digital Pumpmaster consists of a OCS Operator Control Display and a Programmable Logic Controller with digital and analog I/O, and a Level Transducer. The OCS provides 24 digital I/O, 4 analog inputs, and 2 analog outputs. The Pumpmaster OCS Operator Control Display has a 4.3 inch color display with 65K colors. The Operator selects pre-programmed screens and inputs level start and stop setpoints, time delays, alternation features, and alarm conditions. The OCS Display panel has a 480 X 272 pixel color touch screen. One of the menu screens is the LIFT STATION STATUS. The status screen displays level in feet, plus a bar graph, and pump status. Other menu screens allow the operator to select level setpoints or time delays.





Lift Station Status

Pump Settings

DP2A PUMPMASTER Main Menu Screens

LIFT STATION STATUS, LEVEL AND PUMP STATUS

PUMP SETPOINTS

LEAD PUMP START AND STOP LEVEL SETPOINTS (1/10 foot)

LAG PUMP START AND STOP LEVEL SETPOINTS (1/10 foot)

LEAD PUMP START AND STOP TIME DELAY SETTING (0-90 seconds)

LAG PUMP START AND STOP TIME DELAY SETTING (0-90 seconds)

PUMP ALTERNATOR SETUP

AUTOMATIC ALTERNATION

SET FIXED PUMPING ORDER, PUMP 1 - PUMP 2

SET FIXED PUMPING ORDER, PUMP 2 - PUMP 1

PUMP FAIL DELAY (Fail off, 5-90 seconds)

ALARM SETTINGS

HIGH ALARM SETPOINTS (1/10 foot)

HIGH ALARM TIME DELAY SETTINGS (0-90 seconds)

ALARM HISTORY LIST (Time, date, type of fault, High Level, Pump 1 Fail, Pump 2 Fail)

PUMP HISTORY (Run Time and Pump Start Counter for each pump)

TRANSDUCER INPUT (Zero and Span)

The Programmable Logic Controller has 4 analog inputs, 2 analog outputs, 12 digital inputs and 12 outputs. The analog 4-20ma input is from a Submersible Level Transducer with a range of 0 - 12 or 0 - 24 feet. Pump hand-off-auto control switches are provided for each pump. Pump output relays are provided and are rated 10 amp @ 120/230v.

DIGITAL PUMPMASTER

JUN 2019

MODEL NO.	DESCRIPTION	VOLTAGE	PRICE
DP2A-900-1 DIALER OPTION	2 Pump Controller, 4.3" Color Level Display, Alternator, High Alarm, 0 - 24 FT. Programmable Logic Controller, 12 DI, 12DO, 4 AI, 2 AO, HOA Switches, Output Relays, Nema 12 Enclosure, 16" x 16" x 6". 16 Digital Outputs, 2 Fail Relays with Indicators.	120V	
DP3A-901-1 DIALER OPTION	3 Pump Controller, 4.3" Color Level Display, Alternator, High Alarm, 0 - 24 FT. Programmable Logic Controller, 12 DI, 12DO, 4 AI, 2 AO, HOA Switches, Output Relays, Nema 12 Enclosure, 20" x 20" x 6". 16 Digital Outputs, 3 Fail Relays with Indicators.	120V	
DP4A-902-1 DIALER OPTION	4 Pump Controller, 4.3" Color Level Display, Alternator, High Alarm, 0 - 24 FT. Programmable Logic Controller, 12 DI, 28 DO, 4 AI, 2 AO, HOA Switches, Output Relays, Nema 12 Enclosure, 24" x 24" x 6". 4 Fail Relay with Indicators. TRANSDUCER OPTIONS	120V	
ABM-300-9	Ultrasonic Level Transducer, 1 - 9 FT, 4-20ma C	Output	
ABM-300-16	Ultrasonic Level Transducer, 1 - 16 FT, 4-20ma	Output	
ABM-300-20	Ultrasonic Level Transducer, 1 - 20 FT, 4-20ma	Output	
PT-575	Submersible Pressure Transducer, 0 - 24 FT, 4-20ma Out +/25% Accuracy, with Cable Support. CABLE PER FEET		
PT-PBLT	Submersible Level Transducer, 0-5psi (11.5 ft.), 4-20ma Output, +/25% Accuracy, with 40 foot		
DIGITAL PUMPMASTER ACCESSORIES			
CB-LP H-REL VXH-RED DL-400 DL-800	Control Breaker and Lightning Protection High Alarm Output Relay with Silencer Switch Alarm Light Fixture with Back Box, Red Globe a Dialer 4 Inputs, Program 4 Phone Numbers, Bat Dialer 8 Inputs, Program 8 Phone Numbers, Bat	tery Backup	

All Prices Subject To Change Without Notice

F.O.B. Rogers, MN